

**Parker ServiceJunior  
QCD 3800-SJR**



**The *NEW* ServiceJunior  
Digital Pressure Gauge**

- 50 Times Faster than Previous Model
- 10 msec Scanning Rate
- Measure PSI, bar, mPa, and kPa with One Gauge
- +/- 0.5% Full Scale Accuracy
- Simple Operation
- Peak and Hold Function with Bar Graph Display

## Parker ServiceJunior

The new Parker ServiceJunior captures momentary pressure spikes that are “invisible” to normal liquid-filled gauges. That means the maximum pressure reading it delivers can be trusted as a much truer reflection of the system’s actual condition; so you can identify potential problems better and diagnose their causes faster. All readings are accurate to within +/-0.5%.



## ServiceJunior Features

- Easy to connect and test system pressure using Parker Diagnostic test port couplings
- Robust, dirt resistant housing
- Simple to operate, four key menu
- Four digit backlit display with easy to read large 0.60" characters
- Minimum and maximum graphic display shows pressure peak
- Power status displayed continuously
- Can be used with most hydraulic and pneumatic media
- Measure PSI, bar, mPa, kPa with one gauge

- Accuracy +/- 0.5% of full scale
- Three pressure ranges
- Operating temperature 14° to 122° F
- Fluid temperature -4° to 176° F
- Storage temperature -4° to 140° F
- Auto power off after 15 minutes or "constant on" at the touch of a button
- Zero adjustment function
- 10 msec scanning rate
- Ratings:

Environmental Protection: EN60529 (IP 65)  
Vibration: IEC 60068-2-6/10 – 500Hz: 20g  
Shock: IEC 60068-2-29/50g 11 msec

Measuring Range	ServiceJunior with PD Coupler	ServiceJunior with EMA3 Coupler	ServiceJunior with 1/4" NPT Port	Overload Pressure	Resolution
-14.5 to 250 PSI (-1 to 16 bar)	SCJR-0250-PD	SCJR-0250-EMA	SCJR-0250-4MP	580 PSI	0.1 PSI
0 to 5800 PSI (0 to 400 bar)	SCJR-5800-PD	SCJR-5800-EMA	SCJR-5800-4MP	11,600 PSI	1 PSI
0 to 8700 PSI (0 to 600 bar)	SCJR-8700-PD <sup>1</sup>	SCJR-8700-EMA <sup>2</sup>	SCJR-8700-4MP	17,400 PSI	1 PSI

NOTES: 1. PD Couplers rated to 6,000 PSI max. 2. EMA3 Couplers rated to 9,000 PSI max.



Parker Quick Coupling Division provides the most complete line of hydraulic and pneumatic diagnostic equipment available. For more information please see QCD Catalog 3800.

## Accessories

Part Number	Description
PD240	PD Series diagnostic coupler
SCA-7/16-EMA-3	7/16 -18UNF-2B female to M16X2.0 EMA3 female swivel
SCJA-1/4	7/16 -18UNF-2B female to 1/4" NPT male adapter
PDH-19	19" PD Hose extension to be used with PD nipple interface
SMA3-400	16" hose assembly for EMA M16X2.0 interface
SCC-110	Storage case for one gauge and diagnostic adapters
SCC-120	Storage case for two gauges and diagnostic adapters

## Bulletin QCD 3800-SJR



**Parker Hannifin Corporation**  
Quick Coupling Division  
8145 Lewis Road  
Minneapolis, MN 55427  
PH: (763) 525-4240 FAX: (763) 544-3418  
www.parker.com/quickcouplings

**The World Standard**  
QS-9000/ISO-9001 Certified